



# LED Backlight

# EL BKL / or Without BKL Display Pattern

## PERFORMANCE FEATURES

LC FLUID	<input type="checkbox"/> STN	<input type="checkbox"/> HTN	<input type="checkbox"/> TN
POLARIZER	<input type="checkbox"/> TRANSPARENT	<input type="checkbox"/> REFLECTIVE	<input type="checkbox"/> TRANSMISSIVE
	<input type="checkbox"/> YELLOW	<input type="checkbox"/> BLUE	<input type="checkbox"/> GRAY
	<input type="checkbox"/> LED	<input type="checkbox"/> SIDE	<input type="checkbox"/> EL
VIEWING ANGLE	<input type="checkbox"/> 6:00	<input type="checkbox"/> 12:00	
TEMPERATURE RANGE	<input type="checkbox"/> STANDARD	<input type="checkbox"/> WIDE	

PIN	SIGNAL	PIN	SIGNAL
1	VSS	9	DB6
2	VDD	10	DB7
3	V0	11	DB0
4	RS	12	DB1
5	R/W	13	DB2
6	E	14	DB3
7	DB4	A	LED+
8	DB5	K	LED-

## REVISION RECORD

VER	Date	Modify	Contents	Name	Confirm	Drawn:	Model Name:
1						ALAN	GDM0801C2
2						Checker:	Date:
3						Approved:	2008-08-15
4						UNIT:	mm
5						Page:	1-1

XIAMEN OCULAR OPTICS CO.,LTD